

ECOMAX

SAFETY DATA SHEET

Preparation Date: June 22, 2022 Revision 2 - Replaces May 1, 2017

1. Product and Company Identification

Product Name: **ECOMAX** Cleaning Solvent
Product Description: Non-flammable cleaning solvent mixture
Product General Use: Industrial use solvent for vapor degreasing, ultrasonic cleaning and other applications where worker exposure is controlled. **INDUSTRIAL USE ONLY. NOT FOR CONSUMER SALE OR USE.**
Manufacturer: Enviro Tech International, Inc.
1800 N. 25th Avenue
Melrose Park, IL, 60160
www.envirotechint.com
Emergency Contact: Velocity EHS 24-HR EMERGENCY CONTACT U.S. & Canada, (800) 255-3924 - INTERNATIONAL CALLS: +01-813-248-0585. Non-Emergency (708) 344-6641 Hours: Mon-Fri 8am-4pm CST

2. Hazards Identification

Classification

Skin irritation	Category 2
Eye irritation	Category 2
Carcinogen	Category 2B (IARC)
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Ingestion (Acute Toxicity Oral)	Category 4
Specific target organ toxicity (repeated exposure)	Category 2

Emergency Overview

This product has no flash point and is non-flammable per OSHA and DOT regulations. (OSHA 2021). Vapors may form a flammable mixture at a concentration of 3.8% to 9.5% by volume with air based on 1-bromopropane (ASTM E-681).

Signal Word: Danger

Hazard Statements

H303 May be harmful if swallowed
H315 Causes skin irritation.
H320 Causes eye irritation.
H333 May be harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H360 May damage fertility.
H372 Presumed to have the potential to produce significant nervous system toxicity in humans through prolonged or repeated exposure



Prevention

- P103 Read label before use.
- P102 Keep out of reach of children.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces.
- P211 Do not spray on an open flame or other ignition source.
- P233 Keep container tightly closed.
- P260 Do not breathe vapors.
- P262 Do not get in eyes, on skin or clothing.
- P263 Avoid contact during pregnancy/while nursing.
- P270 Do not eat, drink or smoke when using this product
- P271 Use in a well-ventilated area.
- P273 Avoid release into the environment.
- P280 Wash face, hands and any exposed skin thoroughly after handling.
- P281 Use personal protective equipment as required.
- P282 Wear Viton or Silvershield gloves. DO NOT use natural rubber or cloth gloves when handling this product.
- P284 Wear respiratory protection. Wear full face mask.

Response

- P308 + P313 IF EXPOSED or concerned: Get medical advice/attention
- P305 + P351 + P338 + P337 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337 + P313 If eye irritation persists, get medical advice/attention
- P303 + P361 + P353 + P352 IF ON SKIN: remove immediately all contaminated clothing. Wash with plenty of soap and water.
- P332 + P313 If skin irritation occurs, get medical advice/attention.
- P304 + P340 IF INHALED: Remove individual to fresh air and keep at rest in a position comfortable for breathing.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. DO NOT induce vomiting.
- P306 + P361+ P363 IF ON CLOTHING: remove all contaminated clothing immediately. Wash contaminated clothing before reuse

Storage & Disposal:

- P403 Store in a dry place. Store indoors.
- P404 + P233 Store in a well-ventilated place. Keep tightly closed.
- P501 Dispose of contents/container in accordance with Federal, state and local regulations.

3. Composition and Ingredient Information

1-bromopropane	CAS 106-94-5	> 95.00 % by weight
1,2-butylene oxide	CAS 106-88-7	< 1.00 % by weight
2-butanol	CAS 78-92-2	< 2.00 % by weight
Dimethoxymethane	CAS 109-87-5	< 3.00 % by weight

Specific amounts of components comprise Trade Secrets per 1920.1200(i)(1)

4. First Aid Measures

- INHALATION Remove person to fresh air. Give oxygen if breathing is difficult. Apply CPR respiration if individual is not breathing.

EYE	Flush eyes with water for at least 15 minutes. Seek emergency medical advice.
SKIN	Remove contaminated clothing and shoes. Wash contaminated areas immediately with soap and water. Seek medical advice.
INGESTION	Drink large amounts of water. DO NOT induce vomiting. Seek emergency medical advice. Rinse mouth with water.
NOTE TO PHYSICIAN	Treat symptomatically.

5. Fire Fighting Measures

Flash Point:	None (See Section 9)
LEL/UEL:	3.8% to 9.5% (based on volume 1-BP/air)
Extinguishing Media:	Extinguishing media should be chosen based on surrounding conditions - use carbon dioxide, dry chemical powder, alcohol foam or polymer foam. Water may be effective for cooling but not extinguishing.
Unsuitable Extinguishing Media:	Do not use water jet as an extinguisher, as this will spread the fire.
Hazardous Combustion Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases/vapors such as gaseous hydrogen fluoride (HF), carbonyl fluoride, carbon monoxide and carbon dioxide. May form explosive mixtures with air.
Special Fire Fighting Procedures:	Avoid breathing fire vapors. Keep run-off water out of sewers and water sources. Dike for water control.
Protective Equipment:	Use NIOSH/MSHA approved/equivalent self-contained breathing apparatus in positive pressure mode and full protective clothing must be worn in case of fire. Use water spray or fog to cool exposed equipment and containers.

6. Accidental Release Measures

Personal Precautions:	Wear protective clothing as described in Section 8 of this Safety Data Sheet. Ventilate enclosed areas. Do not walk through spilled material. Avoid direct contact. Avoid contact with skin, eyes, and clothing. Avoid breathing mist, vapors, spray.
Environmental Precautions:	Do not discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material.
Spill Clean Up Methods:	Provide ventilation and confine spill. Do not allow runoff to sewer or waterways. Dam and absorb spillage with sand, sawdust or other absorbent. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Reference to other Sections:	For personal protection, see Section 8. For waste disposal, see Section 13.

7. Handling and Storage

Handling:	Open container carefully - contents may be under pressure. Avoid skin and eye contact. Use Viton or Silvershield gloves for extended protection.
-----------	--

Nitrile, neoprene or butyl gloves offer less protection and should be used for splash protection only. DO NOT use natural rubber or cloth gloves when handling this product. Avoid inhalation of vapors and spray mists. Wear full face mask and NIOSH approved respirator with organic vapor respirator cartridge. Provide adequate ventilation. In use, may form flammable/explosive vapor-air mixture. Handling, storage and use procedures must be carefully monitored to avoid spills or leaks. Contamination that does occur cannot be easily corrected. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

Storage: Store in tightly closed original container in a dry, cool and well-ventilated place. Separate from oxidizing materials. Empty containers retain product residue and can be hazardous. Do not cut, weld, puncture or incinerate container.

8. Exposure Controls and Personal Protection

Exposure Limits	Worker exposure to all chemicals, including this product, should be kept as low as possible at all times. No OSHA PEL has been published for 1-bromopropane. USEPA: An exposure level to 1-BP in the range of 18 to 30 ppm is protective of workers (Federal Register May 30, 2007). ACGIH TLV - .10 ppm for 1-bromopropane. The documentation for the ACGIH 1-BP TLV states that the TLV applies to 1-bromopropane with an iPB content of 0.1 to 0.2 % by weight. The iPB content of 1-bromopropane in this product is shown by GC analysis to be at or below 0.01%, more than an order of magnitude below the iPB level set forth by ACGIH. Therefore, it is questionable whether or not the TLV is applicable to this product.
	2-butanol OSHA PEL 1,500 ppm
	dimethoxymethane OSHA PEL 1,000 ppm ACGIH TLV 1,000 ppm
Respiratory	Wear full face mask with NIOSH/MSHA approved/equivalent organic vapor respirator.
Clothing/gloves	Wear approved gloves when handling this product. Use Viton or Silvershield gloves for extended protection. Nitrile, neoprene or butyl gloves offer less protection and should be used only for splash protection. DO NOT use natural rubber, cloth or synthetic material gloves when handling this product.
Eye Protection	Wear full face mask.
Hygienic Practices	Do not eat, drink or smoke while working with this product. Launder soiled clothes. Provide emergency eye bath and safety shower. Handle in accordance with good industrial hygiene and safety practice.
Engineering Controls	Safety shower, eye wash stations, ventilation systems.

9. Physical Properties

APPEARANCE	Clear, colorless to yellow liquid
ODOR	Characteristic
INITIAL BOILING POINT	155°F (68°C)
FLASH POINT	None ASTM D-56 TCC. ASTM D-92 COC. ASTM D-93 TCC. OSHA - 2021
UPPER/LOWER FLAMMABILITY LIMITS	3.8% to 9.5% (1-BP/air) - estimated
VAPOR PRESSURE, mm Hg	137.5 @ 20°C

SPECIFIC GRAVITY (25°C ± 5°C, H ₂ O = 1)	1.32 ± 0.01
AUTO-IGNITION TEMPERATURE	860°F (460°C) estimated based on 1-BP
DECOMPOSITION TEMPERATURE	860°F (460°C) estimated based on 1-BP

10. Stability and Reactivity

STABILITY	Stable under normal conditions.
CONDITIONS TO AVOID	Avoid open flame, electric arc and other high energy ignition sources. Prolonged contact with free water may result in diminished stabilizer and corrosion.
INCOMPATIBILITY	Incompatible with strong alkalies, oxidizers, bases, reactive metals and natural rubber.
HAZARDOUS DECOMPOSITION	Thermal decomposition produces carbon monoxide, carbon dioxide, and hydrogen bromide.
HAZARDOUS POLYMERIZATION	Will not occur.
REACTIVITY	Organic Peroxide: No; Pyroforic: No; Water Reactive: No

11. Toxicological Information

Carcinogenicity:		NTP	IARC	OSHA
1-bromopropane	Reasonably anticipated to be a human carcinogen		Group 2B	No
1,2-Butylene oxide	No		Group 2B	No

Specific Components:

1-bromopropane

Acute Effects

LD ₅₀ oral rat (male & female):	4,260 mg/kg >2000 mg/kg (OECD 401)
LD ₅₀ dermal rat (male & female):	>2,0000 mg/kg (OECD 402)
LC ₅₀ inhalation rat:	30 min - 50,291 ppm 4 hour - 14,374 ppm 35 mg/l 4 hr OECD 403 Remarks: No mortality observed at this dose.
Skin:	Rabbit (standard method) No skin irritation. (EC)Reg. 1272/2008 Annex VI - Irritating to skin.
Maximization Test - Skin contact	Guinea pig: Did not cause sensitization (OECD 406)
Eyes:	Rabbit (standard method) Irritating to eyes.
Mutagenicity:	in vitro: Multiple Ames tests with and without metabolic activation. NEGATIVE. (OECD 471) in vivo: 1) Transgenic rodent somatic cell gene mutation assay. Mouse (female) - Inhalation. Result: NEGATIVE. (OECD 488). Test results duplicated in subsequent testing. 2) In vivo micronucleus test - rat (male & female) Result: NEGATIVE. (OECD 474)
Reproductive & developmental:	Two-gen inhalation study: Rat, male & female General Toxicity Parent: NOAEL: 100 ppm F ₁ : NOAEL: 100 ppm
Fertility:	NOAEL: 100 ppm
Early Embryonic Development:	NOAEL: 100 ppm
Fetal development:	Pre-/postnatal development - Rat, female - Inhalation
General Toxicity Maternal:	NOEL: 100 ppm
Teratogenicity:	NOEL: 996 ppm
Embryo-fetal toxicity:	NOEL: 100 ppm

Repeated Dose Toxicity

Rat, male and female - 90 day inhalation NOAEC \geq 125 ppm. Liver, Reproductive organs

High concentrations are irritating to the respiratory tract and may cause headache, dizziness, nausea, vomiting or narcosis. Chronic overexposure at high levels may cause adverse effects in the central nervous system, reproductive system, respiratory system, kidney and liver. Persons having pre-existing diseases of the lungs, eyes or skin may have an increased susceptibility to the hazards of excessive exposure.

1,2-Butylene oxide

Acute oral toxicity LD ₅₀ :	Rat - 900 mg/kg
Acute dermal toxicity LD ₅₀ :	Rabbit - > 1,500 - < 2,950 mg/kg
Acute inhalation toxicity LC ₅₀ :	Rat (male & female): 4 Hour, vapor, > 6.3 mg/l.
Skin corrosion/irritation:	Prolonged or repeated contact may cause skin burns and a more severe response if skin is abraded (scratched or cut) or covered (under clothing, gloves). Did not cause allergic skin reactions when tested in guinea pigs.
Eye Irritation:	May cause serious to moderate eye irritation. May cause slight corneal injury.
Specific Target Organ Systemic Toxicity (Single Exposure - Inhalation):	May cause respiratory tract irritation.
Specific Target Organ Systemic Toxicity (Repeated Exposure):	In animals, peripheral nervous system & respiratory tract.
Mutagenicity:	In vitro genetic toxicity studies were positive. Animal genetic toxicity studies were negative.
Carcinogenicity:	Butylene oxide has been shown to produce benign and malignant tumors in rats but not mice. These tumors occurred only following high exposure levels which first produced chronic upper respiratory tract irritation
Reproductive & Developmental:	Limited data in test animals suggest that the material does not affect reproduction. Did not cause birth defects or fetal effects in test animals.

sec butyl alcohol

Oral LD ₅₀ :	>2,193 mg/kg
Dermal LD ₅₀ :	>2,000 mg/kg
Inhalation LC ₅₀ :	> 20 mg/L

dimethoxymethane

Acute toxicity	
LD ₅₀ Oral:	Rat - male and female - 6,423 mg/kg (OECD Test Guideline 423)
LC ₅₀ Inhalation:	Mouse - male and female - 7 h - 57,000 mg/l (OECD Test Guideline 403)
LD ₅₀ Dermal:	Rabbit - male and female - > 5,000 mg/kg (OECD Test Guideline 402)
Skin corrosion/irritation:	Rabbit - No skin irritation - 4 h (OECD Test Guideline 404)
Eye damage/eye irritation:	Rabbit - Mild eye irritation

Respiratory/skin sensitization	Maximization Test - Guinea pig. Result: Did not cause sensitization on laboratory animals. (OECD Test Guideline 406)
Germ cell mutagenicity:	Reverse mutation assay - <i>S. typhimurium</i> . Negative
Carcinogenicity:	Mouse - male and female - Negative IARC: NO NTP: NO OSHA: NO

12. Ecological Information

1-bromopropane

Available data on the organic carbon partition coefficient (K_{OC}) the breakdown processes in water and hydrolysis half-life, and the volatilization half-life indicate that 1-bromopropane is less persistent in the environment than many solvents and would be of low to moderate concern for movement in soil. Based on the LC_{50} , the acute concentration at which 50% of tested animals die, 1-bromopropane's toxicity to aquatic life is moderate, being less than that for ... trichloroethylene, hexane, *d*-limonene and possibly some aqueous cleaners. Based on EPA's criteria for listing under the Toxics Release Inventory (U.S. EPA, 1992), we believe that 1-bromopropane would not be sufficiently toxic to aquatic life to warrant listing under the Toxics Release Inventory. Based on its relatively low bio-concentration factor and $\log K_{OW}$ value, 1-bromopropane is not prone to bioaccumulation. (USEPA - Federal Register May 30, 2007).

K_{OC} , ORGANIC-CARBON PARTITION COEFFICIENT	330
BREAK DOWN IN WATER	Hydrolysis is significant
HYDROLYSIS HALF-LIFE	26 DAYS
VOLATILIZATION HALF-LIFE FROM SURFACE WATERS	3.4 HOURS B 4.4 DAYS
LC_{50} (96 HOURS) FOR FATHEAD MINNOWS	67 mg/l
LOG K_{OW}	2.10
BIOCONCENTRATION FACTOR	23

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

1,2 butylene oxide

Acute toxicity to fish:	Material is slightly toxic to aquatic organisms on an acute basis (LC_{50}/EC_{50} between 10 and 100 mg/L in the most sensitive species tested).
LC_{50}	Leuciscusidus (Golden orfe), static test, 96 Hour > 100 mg/l
Acute toxicity to aquatic invertebrates EC_{50} :	Daphnia magna (Water flea), static test, 48 Hour, 70 mg/l, OECD Test Guideline 202 or Equivalent
Acute toxicity to aquatic plants ErC_{50} :	Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, > 500 mg/l
Toxicity to bacteria EC_{50} :	Activated sludge, static test, 0.5 Hour, Respiration rates, 900 mg/l (OECD 209)
Biodegradability:	Material is readily biodegradable. Passes OECD test for ready biodegradability.
10-day Window:	Pass

Biodegradation:	90%. Exposure time: 28 d. Method: OECD 310 or Equivalent
Theoretical Oxygen Demand:	2.44 mg/mg
Stability in Water (1/2-life)	Hydrolysis, half-life, 11 d
Photodegradation	Atmospheric half-life: 6 days (estimated)
Bioaccumulation:	Does not accumulate in organisms. Bioconcentration potential is low (BCF < 100 or Log Pow < 3).
Partition coefficient:	n-octanol/water (log Pow) - 0.68 at 25 °C
Mobility in soil:	K _{OC} between 0 and 50
Partition coefficient (K _{oc}):	4.49 Estimated.

dimethoxymethane

Toxicity to fish LC ₅₀ :	Danio rerio (zebra fish) - > 1,000 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia/invertebrates:	Immobilization EC50 - Daphnia magna (Water flea) - > 1,200 mg/l - 48 h (OECD Test Guideline 202)
Biodegradability aerobic:	Exposure time 20 - 25 d. Not readily biodegradable.
Bioaccumulative potential:	No data available
Mobility in soil:	No data available
PBT and vPvB assessment:	Assessment not available as chemical safety assessment not required/not conducted
Log Pow:	0 @ 20 C
Log K _{oc} :	0.7439

2-butanol

Ecotoxicity: Fish LC ₅₀	Goldfish: = 4300 mg/L; 24 Hr;
Freshwater Fish	Pimephales promelas: LC ₅₀ : 3670 mg/L/96h
Microtox	Pseudomonas putida: 500 mg/L/16h
Water Flea	EC ₅₀ : 3750 mg/L/24h
If released on soil, sec-butyl alcohol will leach into the ground. It should also volatilize from dry soil and biodegradation will probably be the key process affecting sec-butyl alcohol's fate in soil. If released in water, biodegradation will probably also be the primary factor affecting its loss. In the atmosphere, sec-butyl alcohol will be lost by reaction with photochemically produced hydroxyl radicals. Its estimated half-life is 2 days.	
Physical: Log P(oct) = 0.61	

13. Disposal Considerations

Follow Federal, State and Local governmental regulations. DO NOT flush into sanitary sewer or waterway. Do not reuse empty container.

14. Transportation Information

PROPER SHIPPING NAME : NA3082, Other regulated substances, liquid, n.o.s., (1-bromopropane mixture, non-flammable), 9, III

The above transportation information is valid as of the date of publication of this SDS. Given that regulatory changes are made on an ongoing basis, ETI recommends checking new transportation regulations regularly.

15. Regulatory Information

USMCA	Complies
US TCSA	All of the components of this product are in the TSCA inventory and are active. No substances are subject to a Significant New Use Rule. No substances are subject to TSCA 12(b) export notification requirements.
US RCRA	Not regulate as of the date of this SDS
US HAP	1-bromopropane: YES. CAS 106-94-5 > 95% Federal Register Vol 87. No.3. January 5, 2022 pg. 393 - 396. As of January 5, 2022 [t]his action will have no direct, immediate impacts under 40 CFR part 63 on emissions of 1-BP, but the addition of 1-BP to the HAP list could have immediate impacts to facilities that emit 1-BP (e.g., the operating permits program under Title V of the CAA). USEPA determined that additional guidance may be needed on the listing of 1-BP and intends to publish such guidance upon promulgation of this rule.
US NESHAP	1,2-butylene oxide: YES. CAS 106-88-7 < 1 % weight No regulations specific to 1-bromopropane or 1,2-butylene oxide have been promulgated as of the date of this SDS. It is recommended users follow current NESHAP rules until further regulations are enacted.
VOC	1,320 g/l - 11 lbs/gal
GWP	.31 to 1.57
ODP	.0013
SARA 302	This material does not contain any components with a section 302 EHS TPQ.
SARA 304	This material does not contain any components with a section 304 EHS RQ.
SARA 313	Subject to reporting: 1,2-butylene oxide CAS 106-88-7 < 1 % weight sec-butyl alcohol CAS 78-92-2 < 2 % weight 1-bromopropane CAS 106-94-5 > 95 % weight
SARA 311/312	Hazardous Categorization Acute Health Hazard: Yes Chronic Health Hazard: Yes Fire Hazard: No Sudden Release of Pressure Hazard: No Reactive Hazard: No
CERCLA	40 CFR 302.4 Component: 1,2-butylene oxide CAS 106-88-7 < 1 % weight RQ 100 lbs 1-bromopropane CAS 106-94-5 > 95 % weight RQ 1 lb
US Clean Water Act:	This product does not contain any Hazardous Substances listed under the U.S. Clean Water Act, Section 311/Table 116.4A, Section 311/Table 117.3 or any pollutant listed under the U.S. Clean Water Act Section 307
US SNAP	The Environmental Protection Agency (EPA) approved 1-bromopropane (nPB) as an acceptable substitute for ozone depleting compounds in the precision cleaning sector under the Significant New Alternatives Program (SNAP) Section 612 Clean Air Act. (USEPA - Federal Register May 30, 2007).

STATE REGULATION

1-bromopropane: CA PROP 65: WARNING: Known to the State of California to cause developmental, male and female reproductive effects. Known to the State

of California to cause cancer. CAL/OSHA PEL 5 ppm. CA Airborne Contaminants - 1-bromopropane - Can be absorbed through the skin. Right to Know: Massachusetts: Higher hazard substance under TURA, New Jersey, Pennsylvania.

1,2-Butylene oxide: Right to Know: California Air Toxics Hit Spots A-1 - Present. Massachusetts, New Jersey, Rhode Island, Minnesota. Pennsylvania: To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

2-butanol: Right to Know: California, Massachusetts, New Jersey, Pennsylvania, Minnesota

dimethoxymethane: Right to Know: Massachusetts, New Jersey, Pennsylvania, Rhode Island, Minnesota. CAL OSHA PEL - 1,000 ppm. California Directors List of Hazardous Substances.

International:

1-bromopropane & 1,2 butylene oxide

Canada WHMIS	Class D Division 2B, WHMIS - HC-1
EU EINECS	On or in compliance with the inventory
Australia AICS	On or in compliance with the inventory
Canada DSL	All components Listed
China IECSC	On or in compliance with the inventory.
Japan ENCS\ISHL	On or in compliance with the inventory
Korea KECI (ECL)	On or in compliance with the inventory
New Zealand	Not in compliance with inventory
Philippine PICCS	On or in compliance with the inventory
Taiwan TCSI	On or in compliance with the inventory

1-bromopropane

China On December 1, 2020, regulation GB 38508-2020, *Limits for Volatile Organic Compounds Content in Cleaning Agents* became effective throughout China. Use of 1-bromopropane in China is restricted or prohibited due to VOC content under this regulation. However, the regulation does not apply to such industries as aerospace, nuclear industry, military and semiconductor (including integrated circuit) manufacturing.

dimethoxymethane

EU EINECS	On or in compliance with the inventory
Australia AICS	On or in compliance with the inventory
Canada DSL	On or in compliance with the inventory
Japan ISHL	On or in compliance with the inventory
Korea KECL	On or in compliance with the inventory
New Zealand NZIoC	On or in compliance with the inventory
Philippine PICCS	On or in compliance with the inventory
Taiwan TCSI	On or in compliance with the inventory

2-butanol

Canada WHMIS	Class B2, D2B
EU EINECS	On or in compliance with the inventory
Australia AICS	On or in compliance with the inventory
Canada DSL	On or in compliance with the inventory
China IECSC	On or in compliance with the inventory.
Japan ENCS\ISHL	On or in compliance with the inventory
Korea KECL	On or in compliance with the inventory
Philippine PICCS	On or in compliance with the inventory

16. Other Information

Each user of this product should study this SDS carefully and consult appropriate expertise as necessary to become aware of and understand the data contained in this SDS and any hazards that may be associated with this product. The information provided in this Safety Data Sheet relates only to the specific material designated herein. The user is responsible for determining the conditions of safe use of this product and for complying with all Federal, State and Local governmental laws and regulations concerning its use. The information contained herein is accurate to the best of our knowledge. Enviro Tech International, Inc. makes no warranty, express or implied, including the warranty of merchantability and fitness for a particular purpose, and assumes no liability or responsibility for the accuracy, completeness, timeliness or usefulness of this information. Enviro Tech International, Inc. assumes no liability for any damages incurred, whether directly or indirectly, as a result of any errors, omissions or discrepancies in this information. Enviro Tech International, Inc. assumes no liability for reliance on this data and assumes no liability for damages related to the use or misuse of this product in your process or in combination with other substances.

NFPA Health 2 Flammability 1 Instability 0
HMIS Health 2 Flammability 1 Physical Hazards 0
Preparation Date: Preparation Date: June 22, 2022 Revision 2 - Replaces May 1, 2017
Copyright 2022 Enviro Tech International, Inc.